



RBP Chemical Technology, Inc.

150 S. 118th ST. • P.O. Box 14069
Milwaukee, WI 53214-0069
www.rbpchemical.com
corporate: 800-558-0747
fax: 414-258-7908

Product Data Sheet

Date: 07/27/05
Supersedes: 06/20/00
PRODUCT #: J5130

AQUANOL[®] 300

High Performance Alcohol Replacer

DESCRIPTION: A concentrated high performance alcohol replacer for use on sheetfed and small web continuous type dampening systems. A proven industry standard, **AQUANOL 300** contains wetting agents and solvents for reducing the surface tension of the press ready solution. Compatible with all fountain solutions and additives. Used correctly, **AQUANOL 300** can reduce or completely eliminate the use of alcohol.

SPECIFICATIONS:

Flash Point (TCC):	>210°F (SCC)
Appearance/Odor:	Clear yellow liquid/solvent odor
VOC Content (EPA Method 24):	6.1 lbs./gal.

INSTRUCTIONS: Mix 1 to 4 ounces per gallon of **AQUANOL 300** into the press ready mix. Normal starting dosage is 2 ounces per gallon. To decrease water setting or reduce lead edge toning, increase dosage by 1 ounce per gallon. If ink emulsification or roller stripping occurs decrease dosage by 1 ounce per gallon. For excellent results, use with an RBP **AQUA SERIES** fountain concentrate. Contact RBP technical representative for recommendations.

BENEFITS:

- Lowers the surface tension of press ready solution for maintaining low water settings and good ink/water balance
- Provides excellent ink densities
- Eliminates foaming problems
- Will not harden rollers like isopropyl alcohol
- Low usage rates

This product should be used only for its intended purpose. The information stated above is based on our laboratory tests and experience, and is accurate to the best of our knowledge. Since actual use is beyond our control, the recommendations or suggestions are made without warranty, expressed or implied.